

EUROLITE LED CBT-6 COB TCL Tower

LED light effect column with RGB color mixing, incl. IR remote control

Art. No.: 51930281

GTIN: 4026397670776



The article is no longer in our assortment.

Description:

LED lighting column with RGB color mixing

The flicker-free LED tower EUROLITE LED CBT-6 COB TCL with integrated DMX control unit is equipped with six powerful 30 W COB LEDs in RGB. Thanks to its slim design and the included carrying bag, it is especially suitable for mobile applications, such as solo entertainers or mobile DJs. Thanks to the tripod sleeve, the CBT-6 is suitable for tripod mounting, but you can also place the CBT-6 directly on the floor.

In the auto and music mode you can play integrated show programs. You have direct color selection for 18 colors. Further functions are color change, color fading, dimmer and strobe effects.

The LED light effect column is compatible with QuickDMX, the wireless DMX system from Eurolite. A phantom-powered USB socket for wireless transmission of the DMX signal via a QuickDMX receiver is located on the back of the device.

The integrated control unit with a four-digit LED display allows you to address and adjust the LED tower. The control can be done either by DMX, QuickDMX via USB, by the integrated music control, with the master/slave function or with the included infrared remote control. The P-Con mains connections allow you to easily connect up to eight devices in series.

Features:

- LED tower with integrated DMX control unit and stand sleeve for tripod installation
- 6 LEDs COB (chip-on-board) 3in1 RGB
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; multi beam effect
- Integrated show programs
- Direct color selection for 18 preset colors

Logistic

EAN / GTIN: 4026397670776

Weight: 9,20 kg

Length: 1.04 m

Width: 0.26 m

Height: 0.26 m

- Can be operated in 2; 3; 5; 18; 9; 21 CH mode
- The device is cooled by low-noise cooling fan
- Control via DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 38°
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
Power connection:	Mains input via P-Con (blue), mounting version
Power output:	1 x P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A
Lamp type:	LED lamp
LED type:	6 x COB (chip-on-board) 3in1 RGB
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5; 18; 9; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle:	38°
Beam angle (1/2 peak):	38°
Beam angle (1/10 peak):	70°
Housing color:	Black
Dimensions:	Width: 17 cm Depth: 15 cm Height: 96 cm
Weight:	7.60 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x user manual
- 1 x remote control
- 1 x battery

1 x bag