

EUROLITE LED PIX-144/72 RGB/CW Bar

LED light bar with wide beam SMD LEDs (RGB/CW) and pixel control

Art. No.: 51930353

GTIN: 4026397709650



The article is no longer in our assortment.

Features:

- 144 LEDs SMD 5050 3in1 RGB (homogenous color mix)
 segments controlled separately
- 72 LEDs SMD 5730 cold white (CW)
- Color change adjustable; Dimmer electronic; color blend stepless; color animations with two adjustable colors
- Strobe effect
- 16 integrated show programs
- Can be operated in 6; 16; 84 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 120°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397709650

Weight: 1,94 kg

Length: 1.03 m

Width: 0.12 m

Height: 0.11 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	55 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	144 x SMD 5050 3in1 RGB (homogenous color mix)
	72 x SMD 5730 cold white (CW)
Flash rate:	10 Hz
DMX channels:	6; 16; 84
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; master/slave function; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 108.5 cm
	Depth: 6.5 cm
	Height: 9.0 cm
Weight:	1.63 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x bar
 1 x user manual
 1 x power cord
 2 x mounting bracket
 2 x screw
 2 x washer