

EUROLITE LED Silent Bar 16x4W RGB/WW

Compact and whisper-quiet spotlight for colored and white light

Art. No.: 51930370

GTIN: 4026397731118



Description:

This compact bar is often underestimated, yet it offers several advantages that are not typically expected in this price range. Equipped with 16 LEDs based on red, green, blue, and warm white, it delivers a wide color spectrum as well as convincing white light.

With a total output of 64 watts, it also provides surprisingly strong brightness. At the same time, the bar operates completely fanless, making it ideal for use in noise-sensitive environments.

The beam angle is 20° and can be widened to 30° using the included frost filter. The four LED segments can be controlled individually, offering additional creative flexibility.

Whether for parties, small shows, permanent installations, or theater applications, this bar is highly versatile. It is especially appealing for users who need both warm white and colored light without investing large sums of money.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 16 LEDs 4 W SMD 3535 4in1 RGB/WW
 segments controlled separately
- Color blend stepless; color change automatic; color fade automatic; Dimmer electronic; program speed adjustable
- Wash effect; strobe effect
- 41 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 4; 6; 8; 16; 18; 20 CH mode
- The device is cooled by passive convection cooling

Logistic

EAN / GTIN: 4026397731118

Weight: 3,05 kg

Length: 0.38 m

Width: 0.29 m

Height: 0.14 m

- Control via stand-alone; sound to light via microphone; master/slave function; IR remote control (not included); DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 20°
- Good color rendering index (CRI)
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Video and photography; clubs/dancing school; stage; wedding/gala/events; mobile djs / entertainer; party room; theater; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 1.6 A fuse replaceable
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Lamp type:	LED lamp
LED type:	16 x 4 W SMD 3535 4in1 RGB/WW
Flash rate:	1 - 25 Hz
DMX channels:	4; 6; 8; 16; 18; 20
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; IR remote control (not included); DMX; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Colorchief; Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20° Frost filter 30°
Beam angle (1/10 peak):	50° Frost filter 80°
Color rendering index (CRI):	83 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 33 cm Width: 17 cm

	Depth: 17 cm
Weight:	2.73 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x device
1 x user manual
1 x power cord
1 x frost filter