

EUROLITE LED BAR-6 TCL WW/NW/CW Bar white

LED light effect bar with variable color temperature

Art. No.: 51930380

GTIN: 4026397680737



The article is no longer in our assortment.

Features:

- 6 LEDs 3 W high-power 3in1 CW/NW/WW (homogenous color mix)
- Dimmer electronic
- Strobe effect
- Can be operated in 3; 7 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397680737

Weight: 1,85 kg

Length: 0.54 m

Width: 0.14 m

Height: 0.11 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	15 W
--------------------	------

Fuse:	T 1 A fuse replaceable
-------	------------------------

Lamp type:	LED lamp
------------	----------

LED type:	6 x 3 W high-power 3in1 CW/NW/WW (homogenous color mix)
DMX channels:	3; 7
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Beam angle:	17°
Beam angle (1/2 peak):	17°
Color rendering index (CRI):	93 Ra
Housing color:	White
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 57.0 cm Depth: 8.8 cm Height: 10.9 cm
Weight:	1.66 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0

Scope of delivery:

1 x light effect
 1 x user manual
 1 x power cord
 2 x mounting bracket
 2 x screw
 2 x washer