

## EUROLITE LED BAR-8 SWING QCL bar

Tiltable LED light effect bar with 8 beams and strobe effect

Art. No.: 51930385

GTIN: 4026397711417



**List price: 474.81 €**

incl. 19% VAT.

### Features:

- Vertical inclination angle adjustable
- Dimmer electronic; color fade; color change; color blend adjustable; color selection
- Strobe effect; uplight effect; multi beam effect
- 5 integrated show programs
- Direct color selection for 18 preset colors
- Can be operated in 8; 12; 23; 27; 49 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX via USB (optional); master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; party room; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Standing; suspended
- spotlight**
- 8 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)<BR> LEDs controlled separately
- With a beam angle of 1°
- strobes**
- 175 LEDs 0.2 W SMD 5050 cold white (CW)<BR>7 segments controlled separately
- With a beam angle of 120°

### Logistic

EAN / GTIN: 4026397711417

Weight: 8,15 kg

Length: 1.05 m

Width: 0.14 m

Height: 0.27 m

## Technical specifications:

|                          |                                                                                                                                                                                                                          |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                   |
| Power consumption:       | 80 W                                                                                                                                                                                                                     |
| Protection class:        | Protection class I                                                                                                                                                                                                       |
| Power connection:        | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                                          |
| Power output:            | P-Con (grey), mounting version                                                                                                                                                                                           |
| Fuse:                    | 5 x 20 mm, T 1 A fuse replaceable                                                                                                                                                                                        |
| Lamp type:               | LED lamp                                                                                                                                                                                                                 |
| Max. TILT movement:      | 215° positioning                                                                                                                                                                                                         |
| Flash rate:              | 0.35 - 20 Hz                                                                                                                                                                                                             |
| DMX channels:            | 8; 12; 23; 27; 49                                                                                                                                                                                                        |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                                                           |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                                                           |
| Cooling:                 | Passive convection cooling                                                                                                                                                                                               |
| Control:                 | Stand-alone; IR remote control; DMX; QuickDMX<br>via USB (optional); master/slave function; W-DMX<br>by wireless solution via USB (optional); CRMX by<br>LumenRadio via USB (optional); sound to light via<br>microphone |
| Fixtures available for:  | Colorchief; Light Captain; GDTF (GrandMA3)                                                                                                                                                                               |
| Projection:              | Flicker-free                                                                                                                                                                                                             |
| PWM frequency:           | 7800 Hz                                                                                                                                                                                                                  |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 8183 lx, 3m: 1527 lx, 6m:<br>372 lx<br><br>Cold white (CW) 1m: 66 lx, 3m: 9 lx, 6m: 2 lx                                                                                                             |
| Housing color:           | Black                                                                                                                                                                                                                    |
| Attachment system:       | Mounting bracket                                                                                                                                                                                                         |
| Display type:            | 4 digit 7-segment LED display                                                                                                                                                                                            |
| USB port:                | Type A                                                                                                                                                                                                                   |
| Material:                | Plastic; metal                                                                                                                                                                                                           |
| Dimensions:              | Length: 100.0 cm<br>Depth: 10.7 cm<br>Height: 25.1 cm                                                                                                                                                                    |
| Weight:                  | 7.30 kg                                                                                                                                                                                                                  |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-<br>sensitive environments)                                                                                                                                               |
| Photobiological safety:  | Risk Group 0                                                                                                                                                                                                             |
| LED type:                | 175 x 0.2 W SMD 5050 cold white (CW)                                                                                                                                                                                     |
| Beam angle:              | 120°                                                                                                                                                                                                                     |
| Beam angle (1/2 peak):   | 120°                                                                                                                                                                                                                     |
| LED type:                | 8 x 8 W high-power 4in1 RGBW (homogenous<br>color mix)                                                                                                                                                                   |
| Beam angle:              | 1°                                                                                                                                                                                                                       |
| Beam angle (1/2 peak):   | 1° multicolor                                                                                                                                                                                                            |

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø5mm                                     |
| Material:                | Metal, 3 mm                                             |
| Color:                   | Black                                                   |
| Dimensions:              | Length: 27.5 cm<br>Width: 5.3 cm<br>Height: 8 cm        |
| Weight:                  | 0.39 kg                                                 |
| Cable construction:      | 3 x 1.0 mm² H05VV-F                                     |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |

**Scope of delivery:**

- 1 x light effect
- 1 x mounting bracket
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery