

EUROLITE LED BAR-8 SWING QCL bar

Tiltable LED light effect bar with 8 beams and strobe effect

Art. No.: 51930385

GTIN: 4026397711417



Features:

- Vertical inclination angle adjustable
- Dimmer electronic; color fade; color change; color blend adjustable; color selection
- Strobe effect; uplight effect; multi beam effect
- 5 integrated show programs
- Direct color selection for 18 preset colors
- Can be operated in 8; 12; 23; 27; 49 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX via USB (optional); master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; party room; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Standing; suspended
- **spotlight**
- 8 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
LEDs controlled separately
- With a beam angle of 1°
- **strobes**
- 175 LEDs 0.2 W SMD 5050 cold white (CW)
7 segments controlled separately
- With a beam angle of 120°

Logistic

EAN / GTIN: 4026397711417

Weight: 8,15 kg

Length: 1.05 m

Width: 0.14 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
Max. TILT movement:	215° positioning
Flash rate:	0.35 - 20 Hz
DMX channels:	8; 12; 23; 27; 49
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; QuickDMX via USB (optional); master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone
Fixtures available for:	Colorchief; Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
PWM frequency:	7800 Hz
Illuminance in Lux (lx):	Cold white (CW) 1m: 8183 lx, 3m: 1527 lx, 6m: 372 lx Cold white (CW) 1m: 66 lx, 3m: 9 lx, 6m: 2 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Material:	Plastic; metal
Dimensions:	Length: 100.0 cm Depth: 10.7 cm Height: 25.1 cm
Weight:	7.30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Photobiological safety:	Risk Group 0
LED type:	175 x 0.2 W SMD 5050 cold white (CW)
Beam angle:	120°
Beam angle (1/2 peak):	120°
LED type:	8 x 8 W high-power 4in1 RGBW (homogenous color mix)
Beam angle:	1°
Beam angle (1/2 peak):	1° multicolor

Diameter mounting holes:	3 x Ø11mm; 2 x Ø5mm
Material:	Metal, 3 mm
Color:	Black
Dimensions:	Length: 27.5 cm Width: 5.3 cm Height: 8 cm
Weight:	0.39 kg
Cable construction:	3 x 1.0 mm² H05VV-F
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

- 1 x light effect
- 1 x mounting bracket
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery