

EUROLITE LED PIX-12 SWING QCL Zoom Bar

Art. No.: 51930386

Motorized tiltable LED light effect bar with 12 high-performance LEDs, two zoom ranges from 2° to 28° and 164 effect LEDs



Features:

- 12 LEDs 40 W 4in1 RGBW (homogenous color mix)
 LEDs controlled separately
- 164 LEDs 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
- Positioning within 180° TILT
- Exact 16 bit resolution at Dimmer
- Zoom motor driven
- Color blend stepless; program speed adjustable; color animations with two adjustable colors; dimmer curves with adjustable response; Dimmer speed (step response) adjustable; pulse-width modulation variable
- Beam effect; strobe effect; ambient effect
- 6 integrated show programs
- Can be operated in 28; 34; 67 CH mode
- The device is cooled by cooling fan at the base
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Art-Net; RDM
- Flicker-free
- With a beam angle of 2° - 28° beam
- With a beam angle of 120° ambient light
- With omega bracket
- Monochrome LCD display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397737127

Weight: 17,50 kg

Length: 1.07 m

Width: 0.37 m

Height: 0.19 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	310 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm² H05VV-F
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 40 W 4in1 RGBW (homogenous color mix) 164 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
Max. TILT movement:	180° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 25 Hz
Equipment:	Zoom motor driven
DMX channels:	28; 34; 67
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version
Cooling:	1 x cooling fan at the base
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Art-Net; RDM
Fixtures available for:	Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
DMX fail mode:	Hold; blackout; auto
Beam angle:	120° ambient light 2° - 28° beam
Beam angle (1/2 peak):	Ambient light 120° multicolor
Beam angle (1/2 peak):	Beam 2 - 20°
Beam angle (1/10 peak):	Beam 2 - 28°
Illuminance in Lux (lx):	Narrow red (R) 1m: 8706 lx, 3m: 1789 lx, 6m: 903 lx Narrow green (G) 1m: 12942 lx, 3m: 2762 lx, 6m: 1509 lx Narrow blue (B) 1m: 1924 lx, 3m: 470 lx, 6m: 257 lx Narrow cold white (CW) 1m: 13809 lx, 3m: 2917 lx, 6m: 1573 lx Narrow all 1m: 35732 lx, 3m: 7693 lx, 6m: 4097 lx Wide red (R) 1m: 1884 lx, 3m: 513 lx, 6m: 148 lx Wide green (G) 1m: 3154 lx, 3m: 880 lx, 6m: 256 lx Wide blue (B) 1m: 538 lx, 3m: 152 lx, 6m: 44 lx

Wide cold white (CW) 1m: 3275 lx, 3m: 885 lx,
6m: 257 lx

Wide all 1m: 8576 lx, 3m: 2363 lx, 6m: 682 lx

Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Monochrome LCD display
USB port:	Type A
Transport aid:	4 x rubber feet
Material:	Metal, painted
Dimensions:	Width: 100 cm Depth: 12 cm Height: 28.5 cm
Weight:	15.70 kg

Scope of delivery:

1 x light effect
1 x user manual
1 x power cord
2 x omega bracket