

EUROLITE LED BAR-12 QCL RGB+WW Bar

LED light effect bar (1 m) with RGB+WW color mixing

Art. No.: 51930388

GTIN: 4026397716146



List price: 177.31 €

incl. 19% VAT.

Features:

- 12 LEDs 7 W high-power 4in1 RGB/WW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - 3 integrated show programs
 - Direct color selection for 20 preset colors
 - Can be operated in 2; 4; 5; 6; 9 CH mode
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Flicker-free
 - With a beam angle of 20°
 - Variable color temperature 2700 K - 8000 K
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
 - Silent operation
 - Application possibility: Suspended
- knurled screw**
- M6 thread

Logistic

EAN / GTIN: 4026397716146

Weight: 3,12 kg

Length: 1.03 m

Width: 0.11 m

Height: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 7 W high-power 4in1 RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light Captain; Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	33°
Color temperature:	2700K - 8000K adjustable
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 106.00 cm Depth: 8.85 cm Height: 10.90 cm
Weight:	2.68 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm
Color:	Black, matte
Diameter mounting holes:	1 x Ø9mm
Material:	Plastic, 3 mm
Color:	Black

Dimensions:	Diameter: Ø 2 cm
Thread:	M6 thread x 18 mm

Scope of delivery:

1 x bar
1 x user manual
1 x power cord
2 x mounting bracket
2 x washer
2 x knurled screw