

EUROLITE LED STP-7 Beam/Wash Bar

LED light bar with 7 LEDs for beam and 7 LEDs for wash effects

Art. No.: 51930390

GTIN: 4026397616279



Description:

Beam and wash in one bar

Narrow and wide beams: with the STP-7 light bar from Eurolite, you kill two birds with one stone. This gives you the flexibility to create different moods with just one device.

Light bars are indispensable on many stages. They are used, for example, as uplights, blinders or front lights. However, most bars radiate with only one fixed beam angle - not the STP-7.

Different LEDs

The light bar combines wide-angle LEDs for mood lighting and very tight-angle LEDs for beams and structures. 7 LEDs are used for each of the different versions. The first have a beam angle of 40°. Thanks to RGB color mixing, you can create a colorful atmosphere. From this basic mood, the other LEDs then shoot narrow, white beams with an angle of 2° into the room. The latter can also be controlled individually to make your shows more versatile and flexible.

Intelligent design without gaps

The bar is one meter long and weighs 4 kilograms. Beam and wash LEDs are arranged in alternating order. The design of the bar allows you to connect several devices without gaps. These then look like one large bar. A generous bracket with various mounting positions is available for mounting. You can also use this as a stand. The power connection is made via a P-Con connection, the signal can be looped through. The DMX connections are three-pole.

Select your control unit

The bar offers 6 different DMX modes. In addition, you can select different colors and color mixes directly on the bar. You will also find various stand-alone and music-controlled programs that run automatically. Synchronize several bars in the self-running modes by connecting them according to the master/slave principle.

Logistic

EAN / GTIN: 4026397616279

Weight: 4,65 kg

Length: 1.05 m

Width: 0.23 m

Height: 0.12 m

Features:

- 7 LEDs 3 W high-power cold white (CW)
 LEDs controlled separately
- 7 LEDs 7 W high-power 3in1 RGB (homogenous color mix)
- Color selection; color blend stepless; Dimmer electronic
- Atmospheric effect
- Can be operated in 3; 6; 4; 10; 12; 15 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- With a beam angle of 2° spot
- With a beam angle of 40° wash effect
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; restaurants, bars and hotels; rental
- Application possibility: Standing; suspended

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	180 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 1.6 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 3 W high-power cold white (CW) 7 x 7 W high-power 3in1 RGB (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 6; 4; 10; 12; 15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	2° spot; 40° wash effect
Beam angle (1/2 peak):	Spot 2° Wash effect 40°
Beam angle (1/10 peak):	Wash effect 71°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 100 cm Depth: 12 cm Height: 14 cm

Weight:	3.90 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x user manual
- 1 x mounting bracket