

## EUROLITE LED BAR-6 QCL RGB+UV Bar

LED bar (60cm) with 6 x 4 watt 4in1 RGB/UV LED

Art. No.: 51930394

GTIN: 4026397646405



### Features:

- 6 LEDs 4 W high-power 4in1 RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 20 preset colors
- Can be operated in 2; 4; 5; 9; 6 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRM by LumenRadio via USB (optional)
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

### Logistic

EAN / GTIN: 4026397646405

Weight: 1,95 kg

Length: 0.56 m

Width: 0.12 m

Height: 0.12 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 14 W

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug included                                                                                            |
| Power output:            | 1 x IEC connector (F) mounting version                                                                                                                                                    |
| Lamp type:               | LED lamp                                                                                                                                                                                  |
| LED type:                | 6 x 4 W high-power 4in1 RGB/UV (homogenous color mix)                                                                                                                                     |
| Flash rate:              | 0 - 20 Hz                                                                                                                                                                                 |
| DMX channels:            | 2; 4; 5; 9; 6                                                                                                                                                                             |
| DMX input:               | 1 x 3-pin XLR (M) mounting version                                                                                                                                                        |
| DMX output:              | 1 x 3-pin XLR (F) mounting version                                                                                                                                                        |
| Cooling:                 | Passive convection cooling                                                                                                                                                                |
| Control:                 | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:  | LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                         |
| Projection:              | Flicker-free                                                                                                                                                                              |
| Beam angle (1/2 peak):   | 20°                                                                                                                                                                                       |
| Beam angle (1/10 peak):  | 33°                                                                                                                                                                                       |
| Housing color:           | Black                                                                                                                                                                                     |
| Attachment system:       | Mounting bracket                                                                                                                                                                          |
| Display type:            | 4 digit 7-segment LED display                                                                                                                                                             |
| Dimensions:              | Length: 60 cm<br>Depth: 6.5 cm<br>Height: 10.3 cm                                                                                                                                         |
| Weight:                  | 1.75 kg                                                                                                                                                                                   |
| Noise classification:    | Class 0 (no noise at all)                                                                                                                                                                 |
| Photobiological safety:  | Risk Group 0                                                                                                                                                                              |
| Cable construction:      | 3 x 0.75 mm² H05VV-F                                                                                                                                                                      |
| Cable length:            | Approx. 1.1 m                                                                                                                                                                             |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm                                                                                                                                                  |
| Material:                | Metal, 2 mm                                                                                                                                                                               |

## Scope of delivery:

1 x bar  
 1 x power cord  
 2 x mounting bracket  
 2 x knurled screw  
 2 x washer  
 1 x user manual