

EUROLITE LED PIX-6 HCL Bar

LED bar (44cm) with 6 x 10 watt 6in1 RGBWA/UV LED

Art. No.: 51930401

GTIN: 4026397588514



Features:

- 6 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect; UV effect
- Can be operated in 4; 6; 9; 36; 38 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 24°
- With mounting bracket
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397588514
Weight: 3,63 kg
Length: 0.48 m
Width: 0.20 m
Heigth: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	66 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp

LED type:	6 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 9; 36; 38
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	24°
Beam angle (1/2 peak):	24°
Beam angle (1/10 peak):	44°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 44 cm Depth: 10.5 cm Height: 15 cm
Weight:	3.31 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x remote control