EUROLITE LED PIX-16 QCL Bar

Compact LED color changing bar with 16 x 8 W 4in1 LED

Art. No.: 51930414

GTIN: 4026397440119





The article is no longer in our assortment.

Features:

- Equipped with sixteen QCL LEDs in the colors red, green, blue and white
- Particularly bright illuminating power of the LEDs
- 4, 6, 7, 11, 19, 64, 67 DMX channels selectable for various applications
- Each LED can be controlled individually
- Programmable color change speed, strobe effect and dimmer
- Strobe effect with 1-18 flashes per second
- RGBW color mixing
- Static colors
- Internal programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Manual, sound or DMX-controlled operation
- For large stage backgrounds in public places, main halls and lounges
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- Sound-controlled via built-in microphone
- Addressing via control panel with LCD screen
- Ready for connection with power-cable and plug
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- Switch-mode power supply, automatic power supply adaption between 100 and 250 volts
- DMX512 control possible via any commercial DMX controller
- Can be operated in 6; 4 CH mode

Logistic

EAN / GTIN: 4026397440119
Weight: 8,00 kg
Length: 1.07 m
Width: 0.26 m
Heigth: 0.15 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
DMX channels:	6; 4
Fixtures available for:	Light´J
Dimensions:	Length: 100 cm Depth: 9 cm Height: 17 cm
Weight:	7.30 kg
Beam angle:	25°
LED number:	16
LED type:	8-W-QCL
DMX channels:	4/6/7/11/19/64/67
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Dimensions (L x W x H):	1000 x 170 x 90 mm

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.