

EUROLITE LED BAR-252 RGB 10mm 20° white

LED bar with 252 LEDs

Art. No.: 51930421

GTIN: 4026397397710



Description:

Small David becomes a light giant!

The story of the little one who is first underestimated because of his height and who suddenly shows off big capabilities and then wins praise and admiration, happens all the time. This also goes for our EUROLITE LED bar. Beside its quite decent size, the guiding of light is immense. Responsible for that are 252 white LEDs which truly convince with their luminosity. They operate best when used as audience lighting. By doing so, the strobe effect and the color-fading are the most impressive features. The LEDs are sound controlled via a microphone, that way they can adjust to the music easily. The LED bar RGB 252/10 is ideal for bands, stages and for solo entertainers, but it can also be used as a decoration element.

Logistic

EAN / GTIN: 4026397397710

Weight: 2,60 kg

Length: 1.09 m

Width: 0.13 m

Height: 0.13 m

Features:

- DMX512 control via regular DMX controller
- Sound-control via built-in microphone
- Stand-alone mode functions adjustable via DIP switches
- Color-change speed and strobe effect adjustable via DIP switches
- Multi-color color-changes
- Master/Slave function
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Illuminants: 252 10 mm LEDs (48 x red, 108 x green and 96 x blue)
- Available in 2 LED beam angles: 20° or 40°
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- Strobe effect
- Can be operated in 12 CH mode

- Control via DMX
- With a beam angle of 20°

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	50.00 W
Lamp type:	LED lamp
DMX channels:	12
Control:	DMX
Fixtures available for:	LED PC-Control 512
Beam angle:	20°
Beam angle (1/2 peak):	20°
Housing color:	White
Dimensions:	Length: 107 cm Depth: 6.5 cm Height: 9 cm
Weight:	2.25 kg
DMX channels:	12
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED number:	252
Beam angle:	20°
Dimensions (L x W x H):	1070 x 65 x 90 mm

Scope of delivery: