

## EUROLITE LED PIX-40 RGB Bar

LED beam bar with narrow beam SMD LEDs (RGB) and pixel control

Art. No.: 51930436

GTIN: 4026397729740



**List price: 224.91 €**

incl. 19% VAT.

### Features:

- 40 LEDs 3 W SMD 3535 3in1 RGB<BR> LEDs controlled separately
- Dimmer electronic; color blend stepless; color animations with two adjustable colors; program speed adjustable
- Beam effect
- 30 integrated show programs
- Direct color selection
- Can be operated in 3; 11; 120 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 2°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; theater
- Silent operation
- Application possibility: Suspended

### Logistic

EAN / GTIN: 4026397729740

Weight: 3,85 kg

Length: 1.05 m

Width: 0.20 m

Height: 0.11 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

|                         |                                                                                                                                                                                      |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power consumption:      | 65 W                                                                                                                                                                                 |
| Protection class:       | Protection class I                                                                                                                                                                   |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug                                                                                                 |
| Power output:           | P-Con (grey), mounting version                                                                                                                                                       |
| Fuse:                   | T 5 A fuse fix in power supply                                                                                                                                                       |
| Lamp type:              | LED lamp                                                                                                                                                                             |
| LED type:               | 40 x 3 W SMD 3535 3in1 RGB                                                                                                                                                           |
| Flash rate:             | 0.7 - 22 Hz                                                                                                                                                                          |
| DMX channels:           | 3; 11; 120                                                                                                                                                                           |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                                       |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                                       |
| Cooling:                | Passive convection cooling                                                                                                                                                           |
| Control:                | Stand-alone; sound to light; master/slave<br>function; DMX; QuickDMX via USB (optional); W-<br>DMX by wireless solution via USB (optional);<br>CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light Captain; Colorchief                                                                                                                                                            |
| Projection:             | Flicker-free                                                                                                                                                                         |
| PWM frequency:          | 12300 Hz                                                                                                                                                                             |
| Beam angle:             | 2°                                                                                                                                                                                   |
| Beam angle (1/2 peak):  | 2°                                                                                                                                                                                   |
| Beam angle (1/10 peak): | 5                                                                                                                                                                                    |
| Housing color:          | Black                                                                                                                                                                                |
| Attachment system:      | Mounting bracket                                                                                                                                                                     |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                                        |
| Dimensions:             | Length: 100.5 cm<br>Depth: 8.0 cm<br>Height: 11.5 cm                                                                                                                                 |
| Weight:                 | 3.25 kg                                                                                                                                                                              |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                                                            |

## Scope of delivery:

1 x light effect  
1 x power cord  
1 x user manual