


## EUROLITE LED PIX-144 RGB Bar

Bar (100 cm) with 144 wide beam SMD LEDs (RGB), 8 segments

Art. No.: 51930439

GTIN: 4026397618037



**List price: 106.98 €**

incl. 19% VAT.

### Features:

- 144 LEDs SMD 5050 3in1 RGB (homogenous color mix)<BR>8 segments controlled separately
- Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- Can be operated in 3; 5; 6; 12; 24; 48 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- **knurled screw**
- M8 thread

### Logistic

EAN / GTIN: 4026397618037

Weight: 1,86 kg

Length: 1.05 m

Width: 0.12 m

Heigth: 0.11 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 25 W

Protection class: Protection class I

|                          |                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------|
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:            | 1 x IEC connector (F) mounting version                                                           |
| Fuse:                    | 5 x 20 mm, T 1 A fuse replaceable                                                                |
| Lamp type:               | LED lamp                                                                                         |
| LED type:                | 144 x SMD 5050 3in1 RGB (homogenous color mix)                                                   |
| Flash rate:              | 0.8 - 24 Hz                                                                                      |
| DMX channels:            | 3; 5; 6; 12; 24; 48                                                                              |
| DMX input:               | 3-pin XLR (M) mounting version                                                                   |
| DMX output:              | 3-pin XLR (F) mounting version                                                                   |
| Cooling:                 | Passive convection cooling                                                                       |
| Control:                 | DMX; sound to light via microphone                                                               |
| Fixtures available for:  | Light´ J; LED PC-Control 512; Light Captain; Colorchief                                          |
| Projection:              | Flicker-free                                                                                     |
| PWM frequency:           | 13300 Hz                                                                                         |
| Housing color:           | Black                                                                                            |
| Attachment system:       | 2x mounting bracket                                                                              |
| Display type:            | 4 digit 7-segment LED display                                                                    |
| Material:                | Aluminum casting                                                                                 |
| Dimensions:              | Length: 102 cm<br>Depth: 6.5 cm<br>Height: 8 cm                                                  |
| Weight:                  | 1.54 kg                                                                                          |
| Noise classification:    | Class 0 (no noise at all)                                                                        |
| Cable construction:      | 3 x 0.75 mm² H05VV-F                                                                             |
| Cable length:            | Approx. 1.2 m                                                                                    |
| Diameter mounting holes: | 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8.5mm                                                                  |
| Material:                | Metal, 2 mm                                                                                      |
| Thread:                  | M8 thread x 16 mm                                                                                |
| Material:                | Rubber                                                                                           |
| Dimensions:              | Height: 0.3 cm<br>Diameter: Ø 2 cm                                                               |

### Scope of delivery:

1 x light effect  
 1 x power cord  
 2 x mounting bracket  
 2 x knurled screw  
 2 x washer  
 1 x user manual