EUROLITE LED BAR-1250 RGB+UV 4in1

LED bar (110cm) with 12 x 5 watt 4in1 RGB/UV LED

Art. No.: 51930440

GTIN: 4026397572285





Features:

- Equipped with twelve QCL LEDs in the colors red, green, blue and UV
- 1, 3, 4, 6, 7 or 12 DMX channels selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Additional controlling possibility via the EUROLITE IR-8 remote control, included in delivery
- Functions: Static colors, RGBUV color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Every LED group (each with 4 LEDs) can be controlled individually in 12CH mode
- Sound-control via built-in microphone
- Hanging as well as standing installation possible
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- Ready for connection via enclosed IEC power cord with safety-plug
- 12 LEDs 5 W high-power 4in1 RGB/UV (homogenous color mix)
- Strobe effect; UV effect
- Can be operated in 1; 3; 4; 6; 7; 12 CH mode
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 20°

Logistic

EAN / GTIN: 4026397572285

Weight: 3,57 kg

Length: 1.09 m

Width: 0.12 m

Heigth: 0.13 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 5 W high-power 4in1 RGB/UV (homogenous color mix)
DMX channels:	1; 3; 4; 6; 7; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	38°
Housing color:	Black
Dimensions:	Length: 110 cm Depth: 8 cm Height: 6.2 cm
Weight:	3.19 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x remote control

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.