EUROLITE LED Techno Strobe 250 SMD Sound

Compact strobe with 74 bright SMD LEDs, adjustable flash frequency and sound control

Art. No.: 52200832

GTIN: 4026397758993











List price: 53.43 €

incl. 19% VAT.

Description:

This compact strobe effect is equipped with 74 white LEDs and perfectly suited for your private party room. It can be operated in automatic mode as well as by sound control (via the built-in microphone).

Thanks to the mounting bracket, it can easily be mounted to a wall or ceiling. The flash frequency and the microphone sensitivity can be adjusted via rotary controls.

Logistic

EAN / GTIN: 4026397758993
Weight: 0,50 kg
Length: 0.14 m
Width: 0.14 m
Heigth: 0.20 m

Features:

- Strobe effect
- Flash frequency steplessly adjustable
- Control via stand-alone; sound to light; rotary dial for microphone sensitivity
- Lightweight plastic housing
- With a beam angle of 80° strobe effect
- 74 LEDs 0.4 W SMD 5050
- With mounting bracket
- Various versions available
- The device is cooled by passive convection cooling
- For application areas such as: Party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Technical specifications:

Power supply:	230 V AC, 50 Hz

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power consumption:	8 W
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable length:	Approx. 0.8 m
LED type:	74 x 0.4 W SMD 5050
Flash rate:	0.5 - 14 Hz
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light; rotary dial for microphone sensitivity
Beam angle:	80° strobe effect
Beam angle (1/2 peak):	Strobe effect 80° monochrome
Beam angle (1/10 peak):	Strobe effect 120°
Color temperature:	9000K
Color rendering index (CRI):	82 Ra
Lamp life:	50000 h
Housing color:	Black matte
Attachment system:	1x mounting bracket
Dimensions:	Length: 18 cm Width: 16.5 cm Height: 13.5 cm Diameter: Ø 13.5 cm
Weight:	0.41 kg
Diameter mounting holes:	1 x Ø10mm
Material:	Plastic, 5 mm

Scope of delivery:

1 x device
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.