

EUROLITE LED Strobe SMD PRO 132 DMX RGB

Multifunctional strobe/flood/blinder with 132 bright SMD RGB LEDs

Art. No.: 52200913

GTIN: 4026397630060



List price: 136.85 €

incl. 19% VAT.

Description:

The LED Strobe SMD PRO 132 DMX RGB combines three functions in one fixture: It is equipped with 132 bright RGB SMD LEDs for both dynamic strobe effects and slower blinder effects. Depending on the selected DMX mode, you can choose from up to 15 preset colors for wash effects. The built-in SMD LEDs are flicker-free and therefore the effect can also be used in a TV studio.

The fixture has an auto, music, master/slave and DMX mode and incorporates 3-pin DMX connectors as well as an IEC input to connect it to the mains. The flash frequency and duration is variably adjustable. For a structured and versatile use, you can choose from 7 different DMX modes with 1, 2x2, 3x3, 4, or 6 DMX channels respectively.

Features:

- 132 LEDs 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
- Dimmer electronic; color blend stepless; color change adjustable; pulse effect adjustable
- Strobe effect; wash effect; Blinder effect
- Direct color selection for 15 preset colors
- Can be operated in 1; 2; 3; 4; 6 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 70°
- With mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397630060

Weight: 2,00 kg

Length: 0.39 m

Width: 0.16 m

Height: 0.18 m

- Very quiet working noise
- Application possibility: Suspended

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	132 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
Flash rate:	1 - 30 Hz
DMX channels:	1; 2; 2; 3; 3; 3; 4; 6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
PWM frequency:	15700 Hz
Beam angle:	70°
Beam angle (1/2 peak):	70°
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 35 cm Depth: 7 cm Height: 7.1 cm
Weight:	1.70 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Scope of delivery:

- 1 x light effect
- 1 x user manual
- 1 x power cord
- 1 x XLR cable