


EUROLITE LED Strobe SMD PRO 540 DMX RGB

Multifunctional strobe/flood/blinder with 540 bright SMD RGB LEDs

Art. No.: 52200915

GTIN: 4026397617528



List price: 320.11 €

incl. 19% VAT.

Description:

The LED Strobe SMD PRO 540 DMX RGB combines three functions in one fixture: It is equipped with 540 bright RGB SMD LEDs for both dynamic strobe effects and slower blinder effects.

Depending on the selected DMX mode, the color LEDs can be split in up to 6 individual control segments which can be used to create amazing color effects. You can choose from 17 preset colors. The built-in SMD LEDs are flicker-free and therefore the effect can also be used in a TV studio.

The fixture has 3-pin DMX connectors as well as a P-Con input and output to connect it to the mains. For a structured and versatile use, you can choose from 8 different DMX modes with 2, 3, 4, 5, 7, 9, 18 or 22 DMX channels respectively. Addressing and settings can be made via the built-in control unit or from a distance via the included IR remote control.

Features:

- 540 LEDs SMD 5050 3in1 RGB (homogenous color mix)
6 segments controlled separately
- Color blend stepless; Dimmer electronic
- Strobe effect; wash effect; Blinder effect
- 5 integrated show programs
- Direct color selection for 17 preset colors
- Can be operated in 2; 3; 4; 5; 7; 9; 18; 22 CH mode
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With double bracket
- 4 digit 7-segment LED display

Logistic

EAN / GTIN: 4026397617528

Weight: 3,81 kg

Length: 0.45 m

Width: 0.11 m

Height: 0.33 m

- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; rental
- Very quiet working noise
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	540 x SMD 5050 3in1 RGB (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 5; 7; 9; 18; 22
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 43 cm Depth: 6 cm Height: 25.5 cm
Weight:	3.46 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

- 1 x light effect
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery