

EUROLITE LED Super PIX Strobe 864 Panel

Multifunctional strobe/floodlight/blinder with RGB and cold white LEDs in a total of 11 segments

Art. No.: 52200922

GTIN: 4026397744866



Features:

- 864 LEDs 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
8 segments controlled separately
- 288 LEDs 0.5 W SMD 5050 cold white (CW)
3 segments controlled separately
- Dimmer electronic
- Strobe effect; ambient effect
- 7 integrated show programs
- Direct color selection for 18 preset colors
- Can be operated in 4; 6; 7; 9; 16; 32 CH mode
- The device is cooled by cooling fan
- Control via sound to light via microphone; stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; master/slave function
- Flicker-free
- With a beam angle of 120°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; rental
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397744866

Weight: 6,95 kg

Length: 0.53 m

Width: 0.17 m

Height: 0.40 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 200 W

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05VV-F
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	864 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix) 288 x 0.5 W SMD 5050 cold white (CW)
Flash rate:	0.5 - 20 Hz
DMX channels:	4; 6; 7; 9; 16; 32
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	4 x cooling fan
Control:	Sound to light via microphone; stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	7700 Hz
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	120°
Beam angle (1/2 peak):	120°
Lamp life:	50000 h
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
USB port:	Type A
Diameter mounting holes:	3 x Ø10mm
Material:	Metal
Dimensions:	Width: 46.7 cm Depth: 12.0 cm Height: 32.4 cm
Weight:	6.30 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x light effect
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery