

EUROLITE Multiflood Pro IP SMD RGBW Strobe/Wash MK2

Art. No.: 52200928

Weather-proof (IP65) high-intensity floodlight/strobe, with RGBW color mixing and warm white LED strips GTIN: 4026397755879



Description:

Even the first version of the Multiflood Pro IP SMD was known for its extremely high output: whether used as a strobe, blinder, or wide washlight, it made a strong impression. The new version retains the same weatherproof housing but offers several notable improvements.

The brightness has been further increased. While it uses slightly fewer LEDs, they are significantly more powerful. In addition to the RGBW LEDs, there are now warm white LED strips above and below the main light surface, providing additional strobe and texture effects. These strips can be controlled in 24 segments. The main colored light surface is now divided into 8 segments, allowing for greater creative control.

The connectivity has also been improved: power can now be looped through to additional units. For noise-sensitive environments, a dedicated low-noise mode is available. Another new feature is the adjustable PWM frequency, ensuring flicker-free performance even in demanding film and video applications.

Logistic

EAN / GTIN: 4026397755879

Weight: 14,05 kg

Length: 0.57 m

Width: 0.40 m

Height: 0.25 m

Features:

- 768 LEDs 2 W SMD 6065 4in1 RGBW (homogenous color mix)
8 segments controlled separately
- 216 LEDs 1 W SMD 3030
24 segments controlled separately
- Color change adjustable; dimmer curves adjustable; Dimmer speed (step response) adjustable; color blend stepless
- Blinder effect; strobe effect; ambient effect
- 32 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; master/slave function
- Flicker-free

- RDM For bidirectional communication over the DMX line
- With a beam angle of 120°
- With omega bracket
- OLED display
- Mains input and output for power linking up to 2 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental; architecture
- Very quiet working noise
- Application possibility: Standing; suspended
- Can be operated in 7; 8; 12; 17; 22; 56; 64 CH mode

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	1200 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	768 x 2 W SMD 6065 4in1 RGBW (homogenous color mix) 216 x 1 W SMD 3030
Flash rate:	0.5 - 19 Hz
DMX channels:	7; 8; 12; 17; 22; 56; 64
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	3 x temperature-controlled fan
Control:	Stand-alone; DMX; RDM; master/slave function
Projection:	Flicker-free
DMX features:	RDM For bidirectional communication over the DMX line
DMX fail mode:	Hold; blackout
Beam angle:	120°
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	OLED display
Diameter mounting holes:	2 x Ø12mm
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Width: 49.0 cm Depth: 16.0 cm Height: 28.5 cm
Weight:	12.95 kg

Noise classification:

Class 1 (very slight noise, suitable for noise-sensitive environments) depending on mode used

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
2 x omega bracket
1 x XLR cable