

EUROLITE Multiflood Pro IP SMD RGBW Strobe/Wash

Weather-proof (IP65) 3in1 LED effect light with RGBW color mixing

Art. No.: 52200930

GTIN: 4026397656855



The article is no longer in our assortment.

Features:

- 1320 LEDs 0.4 W SMD 5050 4in1 RGBW (homogenous color mix)
6 segments controlled separately
- Dimmer curves adjustable; color blend stepless; Dimmer electronic
- Strobe effect; wash effect; Blinder effect
- 36 integrated show programs
- Direct color selection for 16 preset colors
- Can be operated in 4; 5; 7; 13; 15; 31 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- With mounting bracket; with omega bracket
- Monochrome LCD display
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397656855

Weight: 14,80 kg

Length: 0.56 m

Width: 0.40 m

Height: 0.25 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	315 W
IP classification:	IP65
Protection class:	Protection class I
Lamp type:	LED lamp

LED type:	1320 x 0.4 W SMD 5050 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 5; 7; 13; 15; 31
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle (1/2 peak):	120°
Attachment system:	Mounting bracket 2x omega bracket
Display type:	Monochrome LCD display
Dimensions:	Width: 49 cm Depth: 16 cm Height: 28.5 cm
Weight:	13.70 kg
Noise classification:	Class 4 (loud noises)

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 2 x omega bracket
 1 x XLR cable