

EUROLITE LED IP PIX Strobe FROST

Art. No.: 52200937

Linkable outdoor spotlight (IP65) with stepless electronic frost for stroboscope, ambient and animation effects

GTIN: 4026397752588



List price: 320.11 €

incl. 19% VAT.

Description:

The frost version of the IP Pix Strobe offers several unique features that significantly expand its range of applications. At its core is the electronic frost filter, which can be activated or deactivated via DMX. This allows the beam to be widened dynamically, creating additional creative possibilities.

The housing has also been redesigned: multiple units can now be connected directly to each other, enabling seamless installations. The included bracket is the longer MK2 version for improved handling. In addition, a compact secondary bracket is provided, allowing the fixture to be mounted directly and space-efficiently, for example on a pipe.

The proven LED configuration remains unchanged. A very bright central LED strip offers adjustable color temperature from warm white to cool white and is divided into four controllable segments. This is complemented by RGB LEDs above and below, arranged in eight segments.

With its extremely wide beam angle and excellent visibility from different angles, the fixture can be used as a strobe, a blinder, or for atmospheric lighting. Its fanless design ensures completely silent operation, while the hermetically sealed IP65 housing provides protection against dust and weather, making it suitable for both indoor and outdoor use.

The frost version is available with both 5-pin and 3-pin DMX connectors.

Features:

- 240 LEDs 0.5 W SMD 5050 3in1 RGB
8 segments controlled separately
- 40 LEDs 1 W SMD 3030 2in1 CW/WW
4 segments controlled separately
- Integrated mounting system for toolfree and seamless cluster setups
- Wash effect; strobe effect; ambient effect

Logistic

EAN / GTIN: 4026397752588

Weight: 4,25 kg

Length: 0.42 m

Width: 0.24 m

Height: 0.15 m

- Frost filter electronic stepless; Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; running light adjustable; color animations with two adjustable colors
- 20 integrated show programs
- Variable color temperature 3200 K - 6600 K
- Direct color temperature selection for 35 preset values
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- With a beam angle of 120°
- Good color rendering index (CRI)
- Monochrome OLED display
- With mounting bracket; with omega bracket
- Built with SEETRONIC connector
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; theater; rental; architecture
- The device is cooled by passive convection cooling
- Silent operation
- Application possibility: Suspended; on stand
- IP65
- With pressure compensation membrane
- Can be operated in 7; 11; 19; 25; 26; 32; 33; 35 CH mode
- Mains input and output for power linking up to 8 units

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	180 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	240 x 0.5 W SMD 5050 3in1 RGB 40 x 1 W SMD 3030 2in1 CW/WW
Flash rate:	1 - 25 Hz
DMX channels:	7; 11; 19; 25; 26; 32; 33; 35
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX
Fixtures available for:	Light Captain; GDTF (GrandMA3)
PWM frequency:	4000 Hz
DMX fail mode:	Blackout; hold; auto; manual
Beam angle:	120°
Beam angle (1/2 peak):	120° multicolor
Color temperature:	3200K - 6600K adjustable
Color rendering index (CRI):	80 Ra
Lamp life:	50000 h
Distance to wall:	500 mm
Housing color:	Black matte
Attachment system:	Ø 12mm Mounting bracket

	Ø 12mm Omega bracket
Display type:	1 x monochrome OLED display
Use of brands:	Built with SEETRONIC connector
Material:	Metal, painted
Dimensions:	Length: 38 cm Width: 10.8 cm Height: 17.65 cm
Weight:	3.70 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø12mm
Material:	Metal, painted
Cable construction:	3 x 1.5 mm² H07RN-F
Cable length:	Approx. 1.2 m
Material:	Metal, painted

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x omega bracket