

EUROLITE LED IP Mega PIX Strobe 714 SWING

Outdoor spotlight (IP65) with tilt motor for strobe, blinder and matrix effects

Art. No.: 52200943

GTIN: 4026397746174



List price: 927.01 €

incl. 19% VAT.

Features:

- 126 LEDs 3 W SMD 3535 cold white (CW)
7 segments controlled separately
- 588 LEDs 0.25 W SMD 5050 4in1 RGBW (homogenous color mix)
14 segments controlled separately
- Positioning within 200° TILT
- Dimmer
- Color macros adjustable; Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; color animations with two adjustable colors
- Ambient effect; strobe effect; Blinder effect
- 46 integrated show programs
- Can be operated in 8; 9; 11; 12; 17; 18; 71 CH mode
- The device is cooled by cooling fan at the base; temperature-controlled fan at the head
- Control via DMX; RDM; stand-alone; master/slave function
- Flicker-free
- With a beam angle of 120° matrix effect
- With omega bracket
- Multicolor TFT display
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397746174

Weight: 13,80 kg

Length: 0.61 m

Width: 0.23 m

Height: 0.42 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	365 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm ² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	126 x 3 W SMD 3535 cold white (CW) 588 x 0.25 W SMD 5050 4in1 RGBW (homogenous color mix)
Max. TILT movement:	200° positioning auto position correction (feedback)
Flash rate:	0.5 - 17 Hz
Equipment:	Dimmer
DMX channels:	8; 9; 11; 12; 17; 18; 71
DMX input:	3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 5-pin XLR (F) mounting version IP
Cooling:	1 x cooling fan at the base 2 x temperature-controlled fan at the head
Control:	DMX; RDM; stand-alone; master/slave function
Fixtures available for:	Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
PWM frequency:	4100 Hz
Beam angle:	120° matrix effect
Beam angle (1/2 peak):	Matrix effect 120°
Beam angle (1/10 peak):	Matrix effect 170°
Illuminance in Lux (lx):	All 1m: 9289 lx, 3m: 1238 lx, 6m: 346 lx
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Multicolor TFT display
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Width: 52.5 cm Depth: 14.0 cm Height: 33.5 cm
Weight:	12.85 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

1 x device
1 x user manual
1 x power cord
2 x omega bracket