

EUROLITE LED Mega Strobe 768 Bar

Strobe bar with colored and white pixel LEDs and switchable frost

Art. No.: 52200950

GTIN: 4026397707526



The article is no longer in our assortment.

Features:

- 384 LEDs SMD 3528 cold white (CW)
- 384 LEDs SMD 5050 3in1 RGB (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless; dimmer curves adjustable; frost filter electronic
- Strobe effect; ambient effect
- 37 integrated show programs
- Can be operated in 7; 18; 21; 113; 125; 257; 269 CH mode
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; master/slave function
- Flicker-free
- With mounting bracket
- LCD display
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental
- Very quiet working noise
- Application possibility: Suspended; standing

Logistic

EAN / GTIN: 4026397707526

Weight: 7,40 kg

Length: 1.06 m

Width: 0.14 m

Height: 0.20 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	350 W
--------------------	-------

Protection class:	Protection class I
-------------------	--------------------

Fuse:	T 4 A fuse replaceable
-------	------------------------

Lamp type:	LED lamp
LED type:	384 x SMD 3528 cold white (CW) 384 x SMD 5050 3in1 RGB (homogenous color mix)
Flash rate:	0.3 - 15 Hz
DMX channels:	7; 18; 21; 113; 125; 257; 269
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX; stand-alone; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle (1/2 peak):	Strobe effect 65° Ambient light 50°
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 100 cm Depth: 13.5 cm Height: 8.5 cm
Weight:	6.55 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Scope of delivery:

1 x light effect
1 x power cord
1 x user manual