

EUROLITE LED Neon Stick 134cm RGB

LED color tube with floor stand and IR remote control

Art. No.: 52500222

GTIN: 4026397694796



List price: 59.38 €

incl. 19% VAT.

Features:

- Extraordinary lighting for an enchanting atmosphere
- The milky PVC housing provides for a lovely appearance as well as for atmospheric illumination
- 72 LEDs SMD 5050 3in1 RGB (homogenous color mix)
- Color change adjustable; color fade adjustable; program speed adjustable; Dimmer electronic
- Direct color selection for 16 preset colors
- Control via IR remote control
- With a beam angle of 180°
- For application areas such as: Wedding/gala/events; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; wall mounting

Logistic

EAN / GTIN: 4026397694796

Weight: 0,60 kg

Length: 1.46 m

Width: 0.07 m

Height: 0.07 m

Bulky product

Technical specifications:

Power supply:	12V DC
Power consumption:	Max. 12 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC adapter (provided)
Cable length:	Approx. 0.25 m
Lamp type:	LED lamp

LED type:	72 x SMD 5050 3in1 RGB (homogenous color mix)
Control:	IR remote control
Beam angle:	180°
Beam angle (1/2 peak):	180°
Luminous flux:	219 lm
Housing color:	Semi-transparent
Material:	Plastic
Dimensions:	Length: 134 cm Diameter: Ø 3.1 cm
Weight:	0.44 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	963514
Power supply:	100-240 V AC, 50/60 Hz
Pin configuration:	Inside + / outside -
Protection class:	Protection class II
Cable length:	Approx. 1.7 m
Output:	12 V DC; 1 A; 12 W
Color:	Black
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Material:	Plastic
Color:	Black
Material:	Plastic hard
Color:	Black
Material:	Plastic
Color:	Semi-transparent

Scope of delivery:

1 x light effect
 1 x external mains adapter
 1 x remote control
 1 x stand
 4 x foot
 2 x fixation clip
 6 x screw
 2 x mounting material
 1 x user manual