



Features:

- Rope with thimble and connector
- <p>EUROLITE Steel Rope (SC) 600x3mm black with thimbles
- **Installation rope, safety bond, safety**
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble
- <p>EUROLITE Quick Link Typ A-50 black
- **Quick link**
- Complies with DIN 56927:2009-03

Logistic

Technical specifications:

|                          |                  |
|--------------------------|------------------|
| Secured weight (BGV C1): | Max. 5 kg        |
| Strength classification: | 1770             |
| Temperature range:       | -40° C - +100° C |
| Weight:                  | 0.05 kg          |

**EUROLITE Steel Rope (SC) 600x3mm black with thimbles**

|                                   |                                           |
|-----------------------------------|-------------------------------------------|
| Maximum load WLL (5-fold):        | 100 kg                                    |
| Design of the core:               | 6 x 19 WSC                                |
| Standard:                         | DIN EN 12385-4:2008-06, DIN 56927:2009-03 |
| Nominal tensile strenght of rope: | 1770 N/mm²                                |
| Wire surface:                     | Zinc-plated                               |
| Color:                            | Black                                     |
| Temperature range:                | -40° C - +100° C                          |
| Dimensions:                       | Length: 60 cm<br>Diameter: Ø 0.30 cm      |
| Weight:                           | 0.04 kg                                   |
| Length weigth:                    | 0.0311 kg/m                               |

**EUROLITE Quick Link Typ A-50 black**

|                             |                                                                            |
|-----------------------------|----------------------------------------------------------------------------|
| Maximum load WLL (10-fold): | 50 kg                                                                      |
| Standard:                   | DIN 56927:2009-03,                                                         |
| Shape:                      | A - small opening                                                          |
| Material:                   | Steel, zinc-plated                                                         |
| Opening:                    | 0-5.5 mm                                                                   |
| Dimensions:                 | Length: 2.90 cm<br>Width: 3.50 cm<br>Depth: 1.90 cm<br>Diameter: Ø 0.30 cm |
| Weight:                     | 0.01 kg                                                                    |

**Scope of delivery:**

1 x device