



Description:

EUROLITE Safety bonds
The EUROLITE safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.
The safety bonds are manufactured by a renowned German supplier and are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.
Clearly, every user can secure loads above persons with these safety bonds in all areas where the BGV C1 is required.

Logistic

EAN / GTIN: 4026397496963
Weight: 0,23 kg
Length: 0.50 m
Width: 0.21 m
Heigh: 0.01 m

Features:

- For securing loads over people
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Secured weight (BGV C1):	Max. 35 kg
Maximum load WLL (5-fold):	400 kg

Design of the core:	6 x 19 FC
Strength classification:	1770
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 100 cm Diameter: Ø 0.60 cm
Weight:	0.23 kg
Length weigth:	0.125 kg/m

Scope of delivery:
