SHZ Roundsling with Steel Inlay 3m/4000KG

Roundsling with steel inlay

Art. No.: 58010755

GTIN: 4026397466584









The article is no longer in our assortment.

Features:

- Steelflex with window complies with BGV C1
- For attaching loads
- Made from polyester, complies with DIN EN 1492-2
- Single-coated, thermically fix
- Printed load capacity
- No danger of injury for the hands
- Smooth transport of goods
- Highly flexible
- UV resistant
- Complies with EN 1492-2
- The useful length is 3 m

Logistic

EAN / GTIN: 4026397466584
Weight: 5,25 kg
Length: 0.39 m
Width: 0.39 m
Heigth: 0.07 m

Technical specifications:

Max. load WLL (7-fold):	4000 kg
Standard:	EN 1492-2,
Color:	Black
Temperature range:	-40° C - +100° C
Useable length:	3 m
Weight:	5.25 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.