



BLOCK AND BLOCK SIGMA-30 Truss lifter 120kg 4m

High-quality truss lift for loads up to 120 kg, made in EU

Art. No.: 59000409

GTIN: 4026397644982



The article is no longer in our assortment.

Features:

- Three-part telescopic ground support
- Safety bolts to lock the different sections at different heights
- Locking bolts in the base area to lock the booms
- Booms with adjustable spindle and steel plate with non-slip rubber base
- Corrosion protection through epoxy coating
- Water level to ensure a vertical position
- Earthing connection
- Transport rolls to move the lift when retracted
- AL-KO 351 PLUS winch: Maximum load 350 kg with automatic holding brake. CE declaration of conformity in compliance with the harmonized standards DIN EN 13157, EN 12100 I and II, EC Machinery Directive 2006/42/CE
- Galvanized steel ropes 6x19+1, manufactured in compliance with the standard 13414-1:2004, tensile strength 1770N/mm²
- Material: Carbon steel S-275-J0H, manufactured in compliance with the standards EN10219 and EN10305.5
- Adjustable height
- With BGV-C1 test certificate
- Made in Europe
- With BGV-C1 test certificate

Logistic

EAN / GTIN: 4026397644982

Weight: 36,00 kg

Length: 0.38 m

Width: 0.38 m

Height: 1.61 m

Bulky product

Technical specifications:

Maximum carrying capacity: 120 kg

Minimum load: 25 kg

Nominal tensile strenght of rope:	1770 N/mm²
Height:	Maximum: 400 cm above 3 sections Minimum: 157 cm
Attachment system:	Ø 35mm
Steel rope:	Ø 4 mm
Type (general stands):	Truss lifter
Material:	Steel (powder-coated)
Transport dimensions:	36 cm x 36 cm x 160 cm
Weight:	32.00 kg

Scope of delivery: