EUROLITE STC-400 Lighting stand, 4m

High-quality winch-stand

Art. No.: 59007006

GTIN: 4026397197075









Features:

- Made of steel
- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety-pins for mechanic locking
- One adjustable leg for levelling
- Ideal for mobile, professional lighting-systems or PA-systems
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height

Logistic

EAN / GTIN: 4026397197075
Weight: 23,60 kg
Length: 1.83 m
Width: 0.24 m
Heigth: 0.21 m
Bulky product

Technical specifications:

Maximum carrying capacity:	80 kg
Minimum load:	25 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 410 cm above 3 sections Minimum: 180 cm
Attachment system:	Ø 35mm
Steel rope:	Ø 4 mm
Type (general stands):	Light stand/wind up
Transport dimensions:	180 cm x 21 cm x 19 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Base area:	Ø 146 cm
Weight:	21.70 kg
Type:	Winch-driven stand
Construction:	DIN 15560-27, DIN EN ISO 12100-2
Certified by:	CE
Sections:	3
Maximum load:	80 kg
Minimum load:	25 kg
Maximum height:	4.10 m
Minimum height:	1.80 m
Adapter:	D = 30 mm
Base area:	D = 1.46 m
Transport dimensions:	1.80 x 0.21 x 0.19 m

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.