ALUTRUSS DECOLOCK DQ3-PAC21 2-way Corner 90°

Universal 3-point truss system in lightweight construction

Art. No.: 60301634

GTIN: 4026397209921





Description:

DECOLOCK DQ3 3-point truss system
DECOLOCK DQ3 is a 3-point truss system made of aluminum. The individual elements are connected via three cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The three main chords are made of 35 mm aluminum tube with 2 mm wall thickness and offer sufficient strength at a low weight. The braces have a diameter of 10 mm with 2 mm wall thickness and provide the system with a decorative appearance.

With DECOLOCK, you can realize compact installations with low self weight, e. g. for shop displays, shop decorations, exhibitions, interior design, fair booths, discotheques and theatres.

DECOLOCK is primarily designed for decorative installations and can be used for permanent or temporary installations due to its highly aestethic appearance. The advantages of this system are the compact construction with 220 and 195 mm outer dimensions, low weight, optimum strength along with easy and quick assembly.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

Logistic

EAN / GTIN: 4026397209921
Weight: 1,45 kg
Length: 0.50 m
Width: 0.36 m
Heigth: 0.22 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Features:

- Aluminum alloy for a classic high-tech look
- Fast, efficient and reliable assembly via QUICK-LOCK conical connectors
- An extensive selection of lengths, circular and corner elements offers maximum flexibility
- Special designs according to customer specifications on request
- Trusspipe: 35 mm
- Any RAL color available on request
- Various versions available
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; installation; stage

Technical specifications:

Corner angle:	90°
Trusspipe:	35 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	EN-AW 6060 T66 (AlMgSi0.5)
Color:	Alu colored; any RAL color available on request
Strut diameter x thickness:	10 x 2mm
Dimensions:	Length: 40 cm Width: 40 cm Height: 19.50 cm
Weight:	1.4 kg

Scope of delivery:

1 x connection set

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.