

ALUTRUSS Tower System II

4-point trussing tower complete set

Art. No.: 60304520
GTIN: 4026397570359



List price: 6365.31 €
incl. 19% VAT.

Features:

- For building ground supports with at least 4 towers
- Base with integrated steel T-bar for mounting the hand winch, No. 60304201
- Adjustable height
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>ALUTRUSS Tower Outrigger, long
- The article is delivered pre-assembled
- Trusspipe: 50 mm
- Made in Europe

Logistic

EAN / GTIN: 4026397570359
Weight: 142,80 kg
Length: 1.18 m
Width: 1.00 m
Height: 1.00 m
Bulky product

Technical specifications:

Corner angle:	60°
Weight:	142.32 kg

ALUTRUSS Tower System I

Setup:	Easy installation
--------	-------------------

Maximum carrying capacity:	1000 kg
Height:	Maximum: 700 cm
Trusspipe:	50 mm
Color:	Alu colored
Strut diameter x thickness:	20 x 2mm
Dimensions:	Height: 1050 cm
Weight:	99.52 kg

ALUTRUSS Tower Outrigger, long

Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Material:	Steel; aluminum
Color:	Alu colored; black/yellow
Dimensions:	Length: 117 cm Width: 3.5 cm Height: 34 cm
Weight:	10.70 kg

Scope of delivery:

1 x ALUTRUSS Tower System I

1 x tower
8 x half cone

4 x ALUTRUSS Tower Outrigger, long

1 x device