



Features:

- DMX dimmer pack for truss installation
- Automatic and sound-controlled chase running mode
- Dimmer curves with adjustable response
- Programmable 10 scenes/chases each with max. 30 cues
- Can be operated in 4 CH mode
- Control via RDM; stand-alone; DMX; sound to light via microphone
- 4 digit 7-segment LED display
- For application areas such as: Trade fair and shop fitting; stage; theater; rental
- Very quiet working noise

Logistic

EAN / GTIN: 4026397554564
Weight: 2,75 kg
Length: 0.34 m
Width: 0.25 m
Heigth: 0.14 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Output power:	Max. 1150 W Max. 3680 W
Output current:	Max. 16 A
Power connection:	Fixed power supply cord with safety plug
Power output:	4 x safety contact (F), hinged lid mounting version
Programs:	Programmable 10 scenes/chases each with max. 30 cues
DMX channels:	4

DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	RDM; stand-alone; DMX; sound to light via microphone
Control channels:	4
Attachment system:	2x M8 thread
Display type:	4 digit 7-segment LED display
Status LED:	Channel level meter
Color:	Black
Dimensions:	Width: 28 cm Depth: 19.5 cm Height: 7.5 cm
Weight:	2.50 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Scope of delivery:

- 1 x device
- 1 x user manual