

## EUROLITE DPX-610 S DMX Dimmer Pack

6x10A dimmer for DMX & analog signals with safety out-sockets

Art. No.: 70064122

GTIN: 4026397521719



### Description:

You can dim if you want - Eurolite dimmer pack for professional users

With the DPX-610 S DMX Dimmer Pack by Eurolite you get a digital 6-channel dimmer pack for professional use. Eurolite dimmer packs have been an established part of many stages and events since the early 90's.

DMX or analogue

The device can be controlled analogously or via DMX. The DMX starting address can be set directly on the device. The DPX-610 S can be operated in single-phase or three-phase mode.

Synchronizing multiple devices

You can synchronize multiple devices via DMX. The built-in display and the LED indicators give you a good overview over the different modes.

Setting the lamp pre-heating

The lamp pre-heating can be set individually and directly on the device. One circuit-breaker per channel protects the device from overcurrent.

The channel outputs on the rear panel are designed as safety plugs.

### Logistic

EAN / GTIN: 4026397521719

Weight: 8,65 kg

Length: 0.54 m

Width: 0.49 m

Height: 0.19 m

## Features:

---

- Universal dimmer pack for professional use
- Can be operated 1-phase or 3-phase
- DMX control or analog control possible
- The DMX-starting address can be adjusted on the device
- Synchronization of several devices possible via DMX
- Adjusting the lamp pre-heat
- With automatic circuit breaker per channel
- Channel outputs on the rear panel via safety sockets
- Only for professional use
- Preprogrammed 12 scenes/chases
- Can be operated in 6 CH mode
- Control via analog 0-10 V; stand-alone; DMX
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Trade fair and shop fitting; stage; theater; rental
- Very quiet working noise

## Technical specifications:

---

|                                |                                                                        |
|--------------------------------|------------------------------------------------------------------------|
| Power supply:                  | 230/380 V AC, 50 Hz                                                    |
| Output power:                  | Max. 13800 W<br>Max. 2300 W per channel                                |
| Output current:                | Max. 60 A                                                              |
| Power connection:              | Mains input via screw terminal                                         |
| Power output:                  | 6 x safety contact (F), hinged lid mounting version fused              |
| Power output fuse per channel: | C 10 A fuse resettable                                                 |
| Programs:                      | Preprogrammed 12 scenes/chases                                         |
| DMX channels:                  | 6                                                                      |
| DMX input:                     | 3-pin XLR (M) mounting version                                         |
| DMX output:                    | 3-pin XLR (F) mounting version                                         |
| Control:                       | Analog 0-10 V; stand-alone; DMX                                        |
| Control channels:              | 6                                                                      |
| Color:                         | Black                                                                  |
| Housing design:                | (19") 48.3 cm rack installation 2 U                                    |
| Dimensions:                    | Width: 48.3 cm<br>Depth: 41 cm<br>Height: 8.9 cm                       |
| Weight:                        | 7.30 kg                                                                |
| Noise classification:          | Class 1 (very slight noise, suitable for noise-sensitive environments) |

## Scope of delivery:

---

1 x device  
1 x user manual