EUROLITE DPX-610 MP DMX Dimmer Pack

6x10A dimmer for DMX & analog signals with two 16-pin multipin outs

Art. No.: 70064125

GTIN: 4026397521726











Features:

- Universal dimmer pack for professional use
- Can be operated 1-phase or 3-phase
- The DMX-starting address can be adjusted on the device
- Synchronization of several devices possible via DMX
- Adjusting the lamp pre-heat
- With automatic circuit breaker per channel
- Outputs via two industrial sockets
- Only for professional use
- Preprogrammed 12 scenes/chases
- Can be operated in 6 CH mode
- The device is cooled by temperature-controlled fan
- Control via analog 0-10 V; stand-alone; DMX
- (19") 48.3 cm rack installation 2 U

Logistic

EAN / GTIN: 4026397521726
Weight: 9,00 kg
Length: 0.54 m
Width: 0.51 m
Heigth: 0.20 m

Technical specifications:

Power supply:	230/380 V AC, 50 Hz
Output power:	Max. 2300 W Max. 13800 W
Output current:	Max. 60 A
Power connection:	Mains input via screw terminal
Power output:	2 x 16-pin multi-pin (F) fitted version

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power output fuse per channel:	C 10 A fuse resettable
Programs:	Preprogrammed 12 scenes/chases
DMX channels:	6
Cooling:	Temperature-controlled fan
Control:	Analog 0-10 V; stand-alone; DMX
Control channels:	6
Color:	Black
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48.3 cm Depth: 44.3 cm Height: 8.9 cm
Weight:	7.60 kg

Scope of delivery:

1 x device
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.