

EUROLITE AKKU DMX Operator 30 QuickDMX

Portable, battery-powered DMX controller for 30 channels with QuickDMX transmitter & carrying case

Art. No.: 70064524

GTIN: 4026397750935



List price: 153.51 €

incl. 19% VAT.

Description:

The AKKU DMX Operator 30 is a wireless DMX controller with 6 faders and a large OLED display for operating spotlights and other DMX fixtures. It can transmit up to 30 DMX channels distributed over 5 pages to devices equipped with a QuickDMX receiver and offers 8 memory slots for chases, each with 15 cues. Thanks to its rechargeable battery, it can be used as a portable, handheld device. The housing also allows for wall mounting. DMX cable connections can be established using an adapter cable. The AKKU DMX Operator 30 comes with a USB charging adapter and an XLR adapter cable in a sturdy carrying case.

Logistic

EAN / GTIN: 4026397750935

Weight: 0,85 kg

Length: 0.23 m

Width: 0.18 m

Height: 0.04 m

Features:

- Cordless, flexible and versatile
- Integrated QuickDMX transmitter for wireless DMX control
- Programmable 8 scenes/chases each with 15 cues
- 6 channel faders for adjusting the DMX values in 5 pages
- Fader for master, chase, speed and fade
- Can transmit up to 30 DMX channels
- Wired DMX possible via included adapter cable
- OLED display
- Battery operation up to 9h
- Integrated automatic charging of the battery and status indicator
- Charge status indicator
- QuickDMX: operating range up to 200m in the open air
- Control via DMX; QuickDMX
- Desktop console housing

Technical specifications:

Power supply:	5V DC 1000 mA
Power consumption:	Approx. 5 W
Power connection:	Battery/battery pack via USB C (W) mounting version power supply cord for USB A mains connection included
Battery pack type:	1 x lithium ion 3.6 V, 2600 mAh, 9.36 Wh
Battery pack:	Battery operation up to 9h Recharging time 3.5h via USB
Programs:	Programmable 8 scenes/chases each with 15 cues
DMX channels:	Output 30
DMX output:	1 x USB A (F) mounting version 1 x RJ-45 (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; QuickDMX
Range:	QuickDMX: range up to 200m in the open air
Carrier frequency:	2.4 GHz
Modulation:	GFSK
Control channels:	30
Channel faders:	6
Housing color:	Black matte
Display type:	OLED display
Display reading:	Charge status indicator , bargraph
Control elements:	Power switch, menu
Status LED:	Power, link
Material:	Metal, painted; plastic
Housing design:	Desktop console housing
Dimensions:	Length: 14.5 cm Width: 13 cm Height: 4 cm
Weight:	0.77 kg

Scope of delivery:

1 x controller
1 x user manual
1 x external mains adapter
1 x adapter cable
1 x case
1 x USB cable
1 x declaration of conformity