EUROLITE DMX Commander 512

Modern theater lighting console for 512 DMX channels, separate dimmer faders for scenes & chases

Art. No.: 70064555

GTIN: 4026397724264

Features:

- Designed for moving lights, lighting effects, LED spot lights and dimmers
- Master dimming, fade time and run time easily adjustable
- Different colored fader caps for customized designs included
- Good visual control of scenes and chasers through intelligent status LEDs
- Manual, time-controlled or sound-controlled chase running mode
- Several chases and scenes can be run simultaneously
- Sound control via audio signal or TAP button
- USB port for storing program data
- (19") 48.3 cm rack installation 6 U
- 57 scenes/chases 767 cues distributed over 9 page/s
- Can be operated in 512 CH mode
- Control via sound to light via microphone; sound to light via 6.3 mm jack socket (stereo) mounting version
- LCD display
- The device can be connected via USB to the PC
firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; stage; theater; restaurants, bars and hotels; rental

Logistic

EAN / GTIN: 4026397724264
Weight: 5,40 kg
Length: 0.52 m
Width: 0.37 m
Heigth: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	2 W

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Programs:	57 scenes/chases 767 cues distributed over 9 page/s
DMX channels:	512
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Control:	Sound to light via microphone; sound to light via 6.3 mm jack socket (stereo) mounting version
Housing color:	Black
Display type:	LCD display
Available storage media:	USB devices (FAT 32)
USB port:	2 x type A
PC connect:	Via USB, firmware can be updated
Housing design:	Desktop console housing (19") 48.3 cm rack installation 6 U
Dimensions:	Length: 48.3 cm Width: 26.6 cm Height: 8 cm
Weight:	4.70 kg

Scope of delivery:

1 x device
1 x user manual
1 x power cord
64 x color caps
1 x USB stick

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.