



Features:

- Auto-switching transceiver
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Multicolored LED indicator
- Lockable power input (IP T-Con)
- Control via QuickDMX; plug and play
- Operating range up to 600m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference
- With omega bracket
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397702408
Weight: 1,55 kg
Length: 0.30 m
Width: 0.20 m
Heigth: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	1 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Control:	QuickDMX; plug and play
Range:	Range up to 600m with line-of-sight

Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Attachment system:	Omega bracket
Color:	Black
Dimensions:	Length: 17.3 cm Width: 15.6 cm Height: 9.2 cm
Weight:	1.28 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x declaration of conformity
- 1 x omega bracket