



Features:

- Compact LED controller for controlling RGB and RGBA/RGBW LEDs via Art-Net and DMX
- Converts standard DMX512 signals and Art-Net data to PWM signals for driving LEDs
- For use with the digital LED pixel strip (item 50530200)
- Applicable as standard Art-Net/DMX converter for 1 DMX512 universe (512 channels)
- DMX input and parallel DMX output for serial connection via XLR connectors
- Ethernet port: 2 x RJ45, 10/100 Mbps
- Stand-alone operation possible with 16 built-in light programs
- 2 x 8-digit LCD screen for menu settings
- Terminals for connecting the LEDs
- Powered via included PSU
- Rugged black metal housing
- Can transmit up to 512 DMX channels
- Control via Art-Net
- The device can be connected via RJ-45 (F) mounting version to the PC

Logistic

EAN / GTIN: 4026397543193
Weight: 0,65 kg
Length: 0.23 m
Width: 0.19 m
Heigth: 0.09 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Power consumption:	5 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)

Power output:	Screw plug-in terminal
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version
Control:	Art-Net
PC connect:	Via RJ-45 (F) mounting version
Dimensions:	Width: 15.3 cm Depth: 9 cm Height: 3.7 cm
Weight:	0.47 kg

Scope of delivery:

1 x device
1 x external mains adapter
1 x adapter cable
1 x user manual