

EUROLITE DXT-SP 1in/4out PRO DMX RDM Splitter

RDM-capable DMX splitter, 1in/4out with signal boost

Art. No.: 70064867

GTIN: 4026397572469



The article is no longer in our assortment.

Features:

- DMX splitter for splitting one DMX input signal to 4 DMX outputs
- Input and feed-through output are duplicated on the front and rear panel and connected in parallel
- Switchable filter mode allows all RDM data to be filtered out in order to prevent problems when using fixtures intolerant of RDM
- Bypass function to process signals from older devices similar to DMX signals
- Output frequency adjustable: 22/44 Hz
- Switchable termination resistor
- Outputs galvanically isolated
- Each DMX output can be connected to 32 DMX devices
- Each DMX output with active signal processing
- Control via RDM
- RDM For bidirectional communication over the DMX line
RDM switchable to prevent problems when using fixtures without RDM
- Built with NEUTRIK connector
- Made in Germany

Logistic

EAN / GTIN: 4026397572469

Weight: 1,40 kg

Length: 0.33 m

Width: 0.24 m

Height: 0.06 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12V DC 1000 mA
---------------	--

Power consumption:	3.6 W
--------------------	-------

Power connection:	Mains input via 4-pin screw plug connector (M) mounting version power supply cord with AC adapter (provided)
DMX input:	2 x 3-pin XLR (M) mounting version
DMX output:	4 x 3-pin XLR (F) mounting version separate (galvanic) with active signal processing 2 x 3-pin XLR (F) mounting version Bypass
Control:	RDM
DMX features:	RDM For bidirectional communication over the DMX line RDM switchable to prevent problems when using fixtures without RDM
DMX fail mode:	Hold; blackout; zero values
Use of brands:	Built with NEUTRIK connector
Dimensions:	Width: 27.5 cm Depth: 10 cm Height: 4.1 cm
Weight:	1.21 kg

Scope of delivery:

1 x device
1 x external mains adapter
4 x foot
1 x user manual