

OMNITRONIC PAA-240 PA Amplifier

PA power amplifier, 240 W RMS

Art. No.: 80709809

GTIN: 4026397703696



List price: 415.31 €

incl. 19% VAT.

Features:

- 1 line input (XLR and 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- Master control
- LED indicators for power, level, clip and fault
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397703696

Weight: 7,95 kg

Length: 0.53 m

Width: 0.44 m

Height: 0.18 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	480 W
Protection class:	Protection class I
Output power:	240 W RMS
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Frequency range:	60 - 16000 Hz
S/N ratio:	>90 dB
THD:	<0.5 % at 1 kHz
Impedance:	4-16 ohms; public address systems 100V; Public address systems 70V

Housing color:	Black
Circuitry:	Class AB
Control elements:	Power switch, level control
Controls:	Softstart; overheat; overload; short-circuit; DC voltage
Status LED:	Level meter, power, fault, clip
Connections:	Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR 0.8 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48.3 cm Depth: 26.4 cm Height: 9.8 cm
Weight:	6.55 kg

Scope of delivery:

- 1 x amplifier
- 1 x user manual
- 2 x holder
- 4 x screw