

OMNITRONIC PAP-1000 PA Amplifier

PA power amplifier, 1000 W RMS

Art. No.: 80709830

GTIN: 4026397220919



List price: 1010.31 €

incl. 19% VAT.

Features:

- 1 line input (optionally XLR or 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- Master control
- LED indicators for power, level, clip and fault
- Load detection and power control
- (19") 48.3 cm rack installation 3 U
- Highly efficient air flow from front to rear
- The device is cooled by cooling fan
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397220919

Weight: 27,75 kg

Length: 0.63 m

Width: 0.56 m

Height: 0.21 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	2000.00 W
Protection class:	Protection class I
Output power:	1000 W RMS
Power connection:	Fixed power supply cord with safety plug
Fuse:	6.3 x 32 mm, T 12 A fuse replaceable
Frequency range:	80 - 16000 Hz
S/N ratio:	>90 dB line
THD:	<0.5 % at 1 kHz

Cooling:	2 x cooling fan , air flow from front to rear
Impedance:	4-16 ohms; public address systems 100V; Public address systems 70V
Circuitry:	Class AB
Controls:	Softstart; overheat; overload; short-circuit; DC voltage
Status LED:	Signal, power, fault, clip
Connections:	Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR 0.3 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR
Channels:	Master output: mono, channel control via rotary dial
Material:	Metal
Color:	Black
Housing design:	(19") 48.3 cm rack installation 3 U
Dimensions:	Width: 48.3 cm Depth: 54.7 cm Height: 13.35 cm
Weight:	24.40 kg

Scope of delivery:

1 x amplifier
1 x user manual