

HONEYWELL Projector Speaker L-VBM20A/EN IP65(EN54)
Bidirectional projector speaker

Art. No.: 80710008
GTIN: 4026397518993



Features:

- EN 54-16 certified and EN 60849 compliant
- 2-way coaxial system with 2 x 13 cm woofer (5.25")
- 100 V transformer with 4 power taps
- Intelligible voice and superior sound reproduction
- White grille RAL9003
- Swivel bracket for ceiling or wall mounting
- Indoor and outdoor use (IP65)
- EASE data available in the download section
- Complies with EN 54-24
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397518993
Weight: 3,45 kg
Length: 0.27 m
Width: 0.19 m
Heigh: 0.19 m

Technical specifications:

IP classification:	IP65
Power connection:	Fixed supply cord with open wires
Power:	Program: 30W Rated: 20W RMS
Frequency range:	150 - 20000 Hz
Max. SPL:	92 dB
Impedance:	Public address systems 100V
Standard:	EN 54-24,

Power tapping:	2.5W; 5W; 10W; 20W RMS via no connector/cable only switchable
Speaker:	1 x woofer 5"
Type of speaker:	Projector speaker
Dimensions:	Width: 14 cm Depth: 19.5 cm Height: 14 cm
Weight:	3.20 kg

Scope of delivery: