

OMNITRONIC CST-5 2-way Ceiling Speaker

5" flush-mount speaker, public address systems 100V, 20 W RMS, Ø 17 cm

Art. No.: 80710212

GTIN: 4026397288988



Features:

- 2-way system for excellent sound playback
- Swivel tweeter
- For ceiling thicknesses between 10-40 mm, mounting cut-out ø170 mm
- For speech and background music in indoor PA systems
- Easy installation
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397288988
Weight: 1,55 kg
Length: 0.26 m
Width: 0.23 m
Heigh: 0.10 m

Technical specifications:

Power:	Program: 40W Rated: 20W RMS
Frequency range:	100 - 20000 Hz
Sensitivity:	87 dB
Max. SPL:	96 dB
Impedance:	Public address systems 100V
Setup:	Easy installation
Power tapping:	5W; 10W; 20W RMS via no connector/cable only switchable
Speaker:	1 x full range loudspeaker 5"

Type of speaker:	Flush-mount speaker
Material:	ABS Acrylonitrile butadiene styrene
Color:	White, scratchproof and shockproof
Mounting dimensions:	Ø 17 cm
Dimensions:	Depth: 8 cm Diameter: Ø 20.3 cm
Weight:	1.30 kg

Scope of delivery:

- 1 x speaker
- 1 x user manual