OMNITRONIC CS-6 Ceiling Speaker black

6.5" full-range flush-mount speaker, public address systems 100V, 5 W RMS, Ø 19.5 cm

Art. No.: 80710221

GTIN: 4026397346701









Features:

- For speech and background music in indoor PA systems
- Easy installation
- Black metal grille
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397346701
Weight: 0,87 kg
Length: 0.23 m
Width: 0.08 m
Heigth: 0.23 m

Technical specifications:

Power:	Program: 10W Rated: 5W RMS
Frequency range:	100 - 10000 Hz
Sensitivity:	90 dB (1W/1m)
Max. SPL:	100 dB
Impedance:	Public address systems 100V
Setup:	Easy installation
Power tapping:	1.25W; 2.5W; 5W RMS via spring terminal switchable
Speaker:	1 x full range loudspeaker 6.5"
Type of speaker:	Flush-mount speaker
Material:	ABS Acrylonitrile butadiene styrene

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Color:	Black, scratchproof and shockproof
Mounting dimensions:	Ø 19.5 cm
Dimensions:	Depth: 7 cm Diameter: Ø 23 cm
Weight:	0.74 kg

Scope of delivery:

1 x device
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.