

## OMNITRONIC CST-6 2-way Ceiling Speaker

6" flush-mount speaker, public address systems 100V, 20 W RMS, Ø 20 cm

Art. No.: 80710222

GTIN: 4026397289008



**List price: 59.38 €**

incl. 19% VAT.

### Features:

- 2-way system for excellent sound playback
- Swivel tweeter
- For speech and background music in indoor PA systems
- Easy installation
- White metal grille
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397289008

Weight: 1,90 kg

Length: 0.28 m

Width: 0.25 m

Height: 0.11 m

### Technical specifications:

|                  |                                                              |
|------------------|--------------------------------------------------------------|
| Power:           | Program: 40W<br>Rated: 20W RMS                               |
| Frequency range: | 90 - 20000 Hz                                                |
| Sensitivity:     | 87 dB                                                        |
| Max. SPL:        | 103 dB                                                       |
| Impedance:       | Public address systems 100V                                  |
| Setup:           | Easy installation                                            |
| Power tapping:   | 7.5W; 15W; 30W RMS via no connector/cable<br>only switchable |
| Speaker:         | 1 x woofer 6"<br>1 x tweeter 0.5"                            |

|                      |                                  |
|----------------------|----------------------------------|
| Type of speaker:     | Flush-mount speaker              |
| Material:            | Plastic                          |
| Color:               | White                            |
| Mounting dimensions: | Ø 20 cm                          |
| Dimensions:          | Depth: 9 cm<br>Diameter: Ø 23 cm |
| Weight:              | 1.60 kg                          |

**Scope of delivery:**

- 1 x user manual
- 1 x device