

OMNITRONIC CSH-6 2-way Ceiling Speaker

Art. No.: 80710357

2-way flush-mount coaxial speaker, LF: 6.5" HF: 1", public address systems 100V, 75 W RMS, Ø 24 cm

GTIN: 4026397683509



Features:

- 2-way coaxial system with crossover and PTC tweeter protection
- Durable plastic cabinet with metal grille
- Easy installation
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397683509
Weight: 4,40 kg
Length: 0.33 m
Width: 0.32 m
Heigh: 0.26 m

Technical specifications:

Power:	Program: 150W (8 ohms) Rated: 75W RMS (8 ohms) Rated: 30W RMS (100V PA)
Frequency range:	60 - 20000 Hz
Sensitivity:	88 dB
Impedance:	Public address systems 100V; 8 ohms
Setup:	Easy installation
Power tapping:	3.75W; 7.5W; 15W; 30W RMS via selector switch switchable
Speaker:	1 x woofer 6.5" Voice coil lows 1" 1 x tweeter 1"
Type of speaker:	Flush-mount speaker

Color:	White
Mounting dimensions:	Ø 24 cm
Dimensions:	Depth: 16.2 cm Diameter: Ø 26.7 cm
Weight:	3.25 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x screw plug-in terminal