

OMNITRONIC PS-05 Projector Speaker

Bidirectional speaker (2 x 5") with mount, 100 V 5/10W RMS

Art. No.: 80710362

GTIN: 4026397292374



The article is no longer in our assortment.

Features:

- 100 V speaker system for wall and ceiling installation
- 2 built-in speakers for bidirectional radiation
- Connection cable with 3 power taps
- Weather-proof (IP44), scratch-resistant aluminum housing
- For outdoor and indoor amplifying systems
- Suitable for outdoor use IP44
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397292374

Weight: 3,00 kg

Length: 0.17 m

Width: 0.18 m

Height: 0.25 m

Technical specifications:

IP classification:	IP44
Power:	Program: 20W Rated: 10W RMS
Frequency range:	130 - 15000 Hz
Sensitivity:	91 dB
Max. SPL:	97 dB
Impedance:	Public address systems 100V
Power tapping:	2.5W; 5W; 10W RMS via no connector/cable only switchable
Speaker:	2 x woofer 5"
Type of speaker:	Projector speaker

Dimensions:	Depth: 20.5 cm
	Diameter: Ø 13.8 cm
Weight:	2.6 kg

Scope of delivery: