# OMNITRONIC PS-20 Projector Speaker

Weather-proof 6.5" speaker (IP44) with mount, public address systems 100V, 20 W RMS

**Art. No.: 80710368**


GTIN: 4026397279658











## List price: 117.81 €

incl. 19% VAT.

### Features:

- Durable aluminum cabinet with grille
- With mounting bracket
- Suitable for outdoor use IP44
- For application areas such as: Installation
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397279658
Weight: 2,95 kg
Length: 0.21 m
Width: 0.21 m
Heigth: 0.34 m

### Technical specifications:

| | |
|---|---|
| IP classification: | IP44 |
| Power connection: | Fixed supply cord with open wires |
| Power: | Program: 40W<br>Rated: 20W RMS |
| Frequency range: | 110 - 15000 Hz |
| Sensitivity: | 92 dB (1W/1m) |
| Max. SPL: | 108 dB |
| Impedance: | Public address systems 100V |
| Attachment system: | 1x<br>Mounting bracket |
| Power tapping: | 5W; 10W; 20W RMS via no connector/cable only switchable |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Speaker: | 1 x full range loudspeaker 6.5" |
| Type of speaker: | Projector speaker |
| Material: | Aluminum |
| Color: | White |
| Dimensions: | Depth: 25.2 cm<br>Diameter: Ø 17 cm |
| Weight: | 2.65 kg |

## Scope of delivery:

1 x device
1 x user manual
1 x lid

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.